


Features

- 1.AC inputs.
- 2.High current transfer ratio.
- 3.Opaque type, mini-flat package.
- 4.Subminiature type (The volume is smaller than that of our conventional DIP type by as far as 30%).
- 5.Isolation voltage between input and output Viso:3750Vrms.
- 6.Emloys double transfer mold technology.
- 7.Recognized by UL and CUL, file NO.E225308.
- 8.Approved by VDE 0884 Teil2(NO:40017614).
- 9.Package : 1000Pcs / Reel.
- 10.RoHS Compliant.



Applications

- 1.Hybrid substrates that require high density mounting.
- 2.Programmable controllers.

*PACKAGE DIMENSIONS (UNIT:mm) SMD Type



Internal connection diagram



UNIT : MM[INCH]
TOLERANCE : $\pm 0.5[\pm 0.02]$ UNLESS OTHERWISE NOTED.



*Absolute Maximum Ratings (Ta=25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	IF	±50	mA
	Power dissipation	P	70	mW
Output	Collector-emitter voltage	VCEO	35	V
	Emitter-collector voltage	VECO	6	V
	Collector current	IC	50	mA
	Collector power dissipation	Pc	150	mW
Total power dissipation		P tot	170	mW
*1 Isolation voltage		V iso	3750	Vrms
Operating temperature		T opr	-30 to +100	°C
Storage temperature		T stg	-40 to +125	°C
*2 Soldering temperature		T sol	260	°C

*1 40 to 60%RH, AC for1 minute.

*2 For 10 seconds.

*Electro-optical Characteristics

Parameter			Symbol	Conditions	Min.	Typ.	Max.	Unit
Input	Forward voltage		VF	IF=± 20mA	-	1.2	1.4	V
	Peak forward voltage		VFM	IFM=0.5A	-	-	3.0	V
Output	Collector dark current		ICEO	Vce=20V IF=0	-	-	10 ⁻⁷	A
	Collector-emitter breakdown voltage		BVCEO	IC=0.1mA IF=0	35	-	-	V
	Emitter-collector breakdown voltage		BVECO	IE=10uA IF=0	6	-	-	V
Transfer characteristics	Current transfer ration		CTR	IF=± 1mA Vce=5V	20	-	400	%
	Collector-emitter saturation voltage		VCE (sat)	IF=± 20mA IC=1mA	-	0.1	0.2	V
	Response time	Rise time	tr	Vce=2V IC=2mA RL=100Ω	-	4	18	uS
		Fall time	tf		-	3	18	uS

Model No.	Rank mark	CTR(%)
KB354N1T	A	50 to 150
KB354NT	L	20 to 60
	A	50 to 150
	B	130 to 400

Fig. 1 Current Transfer vs. Forward Current




Fig. 2 Forward Current vs. Forward voltage




Fig. 3 Collector Current vs. Collector-emitter Voltage




Fig. 4 Forward Current vs. Ambient Temperature




Fig. 5 Collector-emitter Saturation Voltage vs. Ambient Temperature





Fig. 6 Response Time vs. Load Resistance



Test Circuit for Response Time




Fig. 7 Collector-emitter Saturation Voltage vs. Forward Current





Fig. 8 Collector Dark Current vs. Ambient Temperature




*NOTES ON HANDLING

1. Cautions regarding noise

Be aware that power is suddenly into the componment any surge current may cause damage happen, even if the voltage is within the absolute maximum ratings.

Reflow Soldering Profile For Lead-free SMT Process.



NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

CAUTION


Within this device there exists GaAs (Gallium Arsenide) material which is a harmful substance if ingested. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them.

RESTRICTIONS ON PRODUCT USE


- The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version. Not all devices / types available in every country.
- We are mention about our product quality stablity, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing KINGBRIGHT products, to observe standards of safety, and to a avoid situations in which a malfunction or failure of a KINGBRIGHT product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that KINGBRIGHT products are used within specified operating ranges as set forth in the most recent products specifications.

Part Number: KB354NT


Outline and Dimension (Tape) (Units : mm)



Tape Direction



Outline and Dimension (Reel)





Packing: 1000pcs/reel

Kingbright

PHOTOCOUPLER

Part Number: KB354NT



<h1>Kingbright</h1>	
P/NO: KB354xxx	
QTY: 1000 pcs	Q.C. <div>Q C XX XX XXXX PASSED</div>
S/N: XXXX	
CODE: XXX	
LOT NO:	
<div>XXXXXXXXXX</div>	
RoHS Compliant	